

DIGIMATIC JOLTING APPARATUS WITH SOUNDPROOF ENCLOSED (AUTOUCH)


Standard: EN 196-1, EN ISO 679

Preparation of 40 x 40 x 160 mm cement mortar prisms

Digimatic Jolting Apparatus is used to compact cement mortar prisms in three gang mould. Made with galvanized chrome steel with quick locking device for prism mould. Easily removable to check weight. Drop height 15 mm with 60 drops per minute cycle. Touch screen control panel with main switch. Built in feed hopper and quick clamp.

Technical Specifications :

Model Number	NL 3006 X / 004
Dimension (mm)	1200 (L) x 490 (W) x 560 (H) mm
Approx. Weight	67 kg
Power	220~240 V, 1 Ph, 50 Hz, 0.4 A




NL 3006 X / 002 - P 001

Unit Consists Of :

Model Number	Parts Description	Qty
NL 3006 X / 004 - P 001	Mould Capping Clamp Set	1 Set
NL 3006 X / 001 - P 002	Scraper (set of 2)	1 Set

*1 Copy of Manual Instruction



NL 3006 X / 001 - A 001

Optional Accessories :

Model Number	Accessories Description
NL 3006 X / 001 - A 001	Three Gang Mould For Prisms 40 x 40 x 160 mm
NL 5001 X / 001 - A 023	Straightedge: 300 x 30 x 2 mm