



Internal Chamber
(Stainless Steel)



Calibration Port



Communication Panel



Pressure System Gauge

HUMIDITY CHAMBER 225 LITRES & 500 LITRES

Standard: EN 196-1, EN 12390-2, EN 12390-9

Temperature & Humidity Control

Constant temperature and humidity testing machine is one of the commonly used equipment in various environmental experiments. This humidity chamber is suitable for various electronic components such as electronic instruments, materials, metals, and electronic products to test their performance & various indicators and quality management in high temperature, low temperature or hot and humid environments.


Technical Specifications :

Model Number	TT 3030 X / 006N	TT 3030 X / 008
Capacity	500 Litres	225 Litres
Temperature Range	0°C ~ 150°C	
Temperature Deviation	±2°C	≤ ±2°C
Humidity Range	20 ~ 98 % RH	
Avg. Heating & Cooling Rate	0.7 ~ 1.0°C / min (under no-load condition)	
Screen Display	7-inch TFT True Color, Resolution 800 x 480	
Chamber Dimension	800(D) x 700(W) x 900(H) mm	500(D) x 600(W) x 750(H) mm
External Dimension	1520(D) x 1000(W) x 1800(H) mm	1450(D) x 880(W) x 1990(H) mm
Packing Dimension	1690(D) x 1210(W) x 1925(H) mm	1620(D) x 1090(W) x 2115(H) mm
Approx. Weight / Packing Weight	524 kg / 624 kg	343 kg / 443 kg
Power Supply	220~240 V, 10 kW, 1 Ph, 50/60 Hz	220~240 V, 1.92 kW, 1 Ph, 50/60 Hz, 10 A, 3-4 Hp

*1 Copy of Manual Instruction

Unit Consists Of :

Model Number	Parts Description	Qty
TT 3030 X / 006N - P 001	Compartment Shelves	2pcs



Humidity Range



Screen Display

Copyright 2026 TESTRONZ. All Rights Reserved. Revision 1 (All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)