
# MISCELLANEDUS

**Civil Engineering Testing Equipment** 

www.nl-test.com





# **HOBO DATA LOGGER RAIN GAUGE**

### Rain Measurer

Record up to 160 in. of rainfall at rates up to 12.7 cm (5 in.) per hour. The Data Logging Rain Gauge system is battery powered and includes a HOBO® Pendant Event data logger with a tipping-bucket rain gauge. Easily collect rainfall, time, and duration data, as well as temperature when used with an optional solar radiation shield (RS1 Solar Radiation Shield, or M-RSA). Base station or shuttle is required.

#### **FEATURES:-**

- \*High quality tipping-bucket rain gauge includes a HOBO Pendant Event data logger. Base station or shuttle is required.
- \*Time and date stamp is stored for each tip provides detail needed to determine rainfall rates and duration.
- \*Reliable, field-proven rain gauge.
- \*Also records temperature when used with an optional solar radiation shield.

# **Technical Specifications:**

Model Number	NL 7065 X / 001
Auternate Code	RG3
Max. Rainfall Rate	12.7 cm (5 in) per hour
Calibration Accuracy	±1.0%
Approx. Weight	1.2 kg

## **Unit Consists Of:**

Model Number	Descriptions	Qty
BASE-U-1	Optic USB Base Station on Coupler	1set
UA-003-64	Pendant Event Data Logger, 64KB	1set
HW-2-1	HOBOware @ 2.1 or later	1set
	(Go to www.onsetcomp.com/hoboware.free.download)	
NL 7065 X / 001 - P 001	Mounting Accessories Set	1set

Copyright 2016 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)