

MSCELLANEDUS Civil Engineering Testing Equipment

www.nl-test.com



GASOLINE GENERATOR

Power Supply

Powered by 4-Stroke OHV petrol engine. Neat and economical for classical design. Circuit breaker protects overload operation. Emergency low oil alert warn the low lube oil level. Large muffler for quiet operation. AVR alternator provides stable voltage and current. Standard configuration of voltmeter.

Technical Specifications:

Model Number	NL 7078 X / 002	NL 7078 X / 003
Alternate Code	LB – 6500 DX	LB – 8000 DXE
AC Output		
Rated Output	5000 W	6000 W
Max. Output	5500 W	6500 W
Engine		
Engine Type	Air-cooled, Single Cylinder, 4-Stroke	
Displacement	389 cc	420 cc
Starting System	Recoil Start / Electric Start	
Ignition System	TCI (Transistor Controlled Igniter)	
Fuel Tank Capacity	25 L	
Oil Capacity	1.1 L	
Noise	74dB (A)	78dB (A)
Dimension	825 x 525 x 545 mm	
Approx. Weight	82 kg	85 kg





Copyright 2023 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 1 (All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)