

THERMOMETER

Temperature Measurement

Width range of temperature measuring thermometer for specific laboratory used.

Technical Specifications :

GLASS TYPE


Model Number	Description	Range
NL 7034 X / 005 A	Glass Thermometer	-10°C to 50°C x 1°C Div.
NL 7034 X / 006	Glass Thermometer	-10°C to 50°C x 0.5°C Div.
NL 7034 X / 009	Glass Thermometer	-10°C to 110°C x 1°C Div.
NL 7034 X / 010	Glass Thermometer	-10°C to 110°C x 0.5°C Div.
NL 7034 X / 011	Glass Thermometer	0°C to 250°C x 1°C Div.
NL 7034 X / 012	Glass Thermometer	-10°C to 300°C x 2°C Div.
NL 7034 X / 019	Glass Thermometer (ASTM 11C/IP28C)	-6°C to 400°C x 2° Div.
NL 2020 X / 001 – A001	Glass Thermometer (ASTM 13C/IP47C)	155°C to 170°C x 0.5°C Div.
NL 2027 X / 001 – A001	Glass Thermometer (ASTM 17C)	19°C to 27° x 0.1°C Div.
NL 2027 X / 001 – A002	Glass Thermometer (ASTM 18C)	34°C to 42°C x 0.1°C Div.
NL 2027 X / 001 – A003	Glass Thermometer (ASTM 19C)	49°C to 57°C x 0.1°C Div.
NL 2027 X / 001 – A004	Glass Thermometer (ASTM 20C)	57°C to 65°C x 0.1°C Div.
NL 2027 X / 001 – A005	Glass Thermometer (ASTM 21C)	79 °C to 87°C x 0.1°C Div.
NL 2027 X / 001 – A006	Glass Thermometer (ASTM 22C)	95°C to 103°C x 0.1°C Div.

DIAL TYPE

Model Number	Description	Range
NL 7034 X / 020	Waterproof Probe Thermometer (Digital)	-49.9°C to 199.9°C x 0.1°C
NL 7034 X / 003	Pocket Dial Thermometer Ø 25 x 127 mm (L)(Tel-Tru,USA)	-10° to 110°C x 1°C Div.
NL 7034 X / 003A	Pocket Dial Thermometer Ø 25 x 127 mm (L)(Tel-Tru,USA)	0 to 250°C x 5°C Div.
NL 7034 X / 004	Dial Laboratory Test Thermometer Ø 45 x 203 mm (L)(Tel-Tru,USA)	-10°C to 110°C x 1°C Div.
NL 7034 X / 004A	Dial Laboratory Test Thermometer Ø 45 x 203 mm (L)(Tel-Tru,USA)	0 to 250°C x 2°C Div.
NL 7034 X / 014	Pocket Dial Thermometer Ø 25 x 130 mm (L)(Eti,UK)	-10°C to 110°C x 2°C Div.
NL 7034 X / 015	Pocket Dial Thermometer Ø 25 x 130 mm (L)(Eti,UK)	-0 to 250°C x 2°C Div.
NL 7034 X / 016	Pocket Dial Thermometer Ø 45 x 130 mm (L)(Eti,UK)	-10°C to 110°C x 1°C Div.
NL 7034 X / 017	Pocket Dial Thermometer Ø 45 x 130 mm (L)(Eti,UK)	-0 to 250°C x 2°C Div.
NL 7034 X / 021	Heavy Duty Dial Thermometer Ø 50 x 300 mm (L)(Eti,UK)	-0 to 120°C x 1°C Div.
NL 7034 X / 022	Heavy Duty Dial Thermometer Ø 50 x 300 mm (L)(Eti,UK)	-0 to 250°C x 2.5°C Div.

NON-CONTACT TYPE

NL 7034 X / 001	Infrared Thermometer	-32°C to 330°C
-----------------	----------------------	----------------



Glass Type



Probe Type



Dial Type



Non-contact Type