THERMOMETER

Temperature Measurement

Width range of temperature measuring thermometer for specific laboratory used.

Technical Specifications :

GLASS TYPE		
Model Number	**Description**	**Range**
NL 7034 X / 005 A	Glass Thermometer	-10°C to 50°C x 1°C Div.
NL 7034 X / 006	Glass Thermometer	-10°C to 50°C x 0.5°C Div.
NL 7034 X / 009	Glass Thermometer	-10°C to 110°C x 1°C Div.
NL 7034 X / 010	Glass Thermometer	-10°C to 110°C x 0.5°C Div.
NL 7034 X / 011	Glass Thermometer	0°C to 250°C x 1°C Div.
NL 7034 X / 012	Glass Thermometer	-10°C to 300°C x 2°C Div.
NL 7034 X / 019	Glass Thermometer (ASTM 11C/IP28C)	-6°C to 400°C x 2° Div.
NL 2020 X / 001 – A001	Glass Thermometer (ASTM 13C/IP47C)	155°C tO 170°C x 0.5°C Div.
NL 2027 X / 001 – A001	Glass Thermometer (ASTM 17C)	19°C to 27° x 0.1°C Div.
NL 2027 X / 001 – A002	Glass Thermometer (ASTM 18C)	34°C to 42°C x 0.1°C Div.
NL 2027 X / 001 – A003	Glass Thermometer (ASTM 19C)	49°C to 57°C x 0.1°C Div.
NL 2027 X / 001 – A004	Glass Thermometer (ASTM 20C)	57°C to 65°C x 0.1°C Div.
NL 2027 X / 001 – A005	Glass Thermometer (ASTM 21C)	79 °C to 87°C x 0.1°C Div.
NL 2027 X / 001 – A006	Glass Thermometer (ASTM 22C)	95°C to 103°C x 0.1°C Div.

DIAL TYPE		
Model Number	**Description**	**Range**
NL 7034 X / 020	Waterproof Probe Thermometer (Digital)	-49.9°C to 199.9°C x 0.1°C
NL 7034 X / 003	Pocket Dial Thermometer Ø 25 x 127 mm (L)(Tel-Tru,USA)	-10° to 110°C x 1°C Div.
NL 7034 X / 003A	Pocket Dial Thermometer Ø 25 x 127 mm (L)(Tel-Tru,USA)	0 to 250°C x 5°C Div.
NL 7034 X / 004	Dial Laboratory Test Thermometer Ø 45 x 203 mm (L)(Tel-Tru,USA)	-10°C to 110°C x 1°C Div.
NL 7034 X / 004A	Dial Laboratory Test Thermometer Ø 45 x 203 mm (L)(Tel-Tru,USA)	0 to 250°C x 2°C Div.
NL 7034 X / 014	Pocket Dial Thermometer Ø 25 x 130 mm (L)(Eti,UK)	-10°C to 110°C x 2°C Div.
NL 7034 X / 015	Pocket Dial Thermometer Ø 25 x 130 mm (L)(Eti,UK)	-0 to 250°C x 2°C Div.
NL 7034 X / 016	Pocket Dial Thermometer Ø 45 x 130 mm (L)(Eti,UK)	-10°C to 110°C x 1°C Div.
NL 7034 X / 017	Pocket Dial Thermometer Ø 45 x 130 mm (L)(Eti,UK)	-0 to 250°C x 2°C Div.
NL 7034 X / 021	Heavy Duty Dial Thermometer Ø 50 x 300 mm (L)(Eti,UK)	-0 to 120°C x 1°C Div.
NL 7034 X / 022	Heavy Duty Dial Thermometer Ø 50 x 300 mm (L)(Eti,UK)	-0 to 250°C x 2°C Div.
NON-CONTACT TYPE		
NL 7034 X / 001	Infrared Thermometer	-32°C to 330°C



Glass Type



Probe Type



Dial Type



Non-contact Type

Copyright 2026 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)